

Smart Power Sensor



Accurate

Class 1 measurement accuracy




Simple & Easy

LCD display, easy to set and check



Energy Efficient

Overall power consumption ≤ 1 W

Technical Specification		DDSU666-H	DTSU666-H
General Data			
Dimension (H x W x D)	100 x 36 x 65.5 mm (3.9 x 1.4 x 2.6 inch)		100 x 72 x 65.5 mm (3.9 x 2.8 x 2.6 inch)
Mounting type	DIN35 Rail		
Weight (including cables)	1.2 kg (2.6 lb)		1.5 kg (3.3 lb)
Power Supply			
Power grid type	1P2W		3P4W
Input power (phase voltage)	176 Vac ~ 288 Vac		
Power consumption	≤ 0.8 W		≤ 1 W
Measurement Range			
Line voltage	/		304 Vac ~ 499 Vac
Phase voltage	176 Vac ~ 288 Vac		
Current	0 ~ 100 A		0 ~ 100 A / 0 ~ 250 A
Measurement Accuracy			
Voltage	±0.5 %		
Current / Power / Energy	±1 %		
Frequency	±0.01 Hz		
Communication			
Interface	RS485		
Baud rate	9,600 bps		
Communication protocol	Modbus-RTU		
Environment			
Operating temperature range	-25 °C ~ 60 °C		
Storage temperature range	-40 °C ~ 70 °C		
Operating humidity	5 %RH ~ 95 %RH (non-condensing)		
Others			
Accessories	RS485 Cable (10 m / 33 ft.)		
	1 CT 100 A / 40 mA (6 m / 19 ft.) 	3 CT 100 A / 40 mA (6 m / 19 ft.) 